

## imageRUNNER ADVANCE C475iF III Series Colour | Compact | Multifunction

Print up to 50 ppm (BW/colour)

Scan up to 100 ipm (300 dpi) (BW/colour, duplex)

Print up to 8-1/2" × 14"

2,300-sheet maximum paper capacity



Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.



### WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive!
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.



### SECURITY

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party Security Information and Event Management (SIEM) systems to help provide real-time comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alterations or tampering.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.<sup>2</sup>



### QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for consistently striking images, thanks to Canon's V<sup>2</sup> colour profile.
- Designed to achieve maximum uptime with status notifications that help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.



## DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



## COST MANAGEMENT

- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-the-minute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



## SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR® certified.

## CONFIGURATION OPTIONS

imageRUNNER ADVANCE C475iF III\*  
(Standard Model)



imageRUNNER ADVANCE C475iFZ III  
(Finisher Model)



### CASSETTE FEEDING UNIT-ASI

- 550-sheet capacity and cabinet for storage
- Supports up to Legal
- Supports 16 lb. Bond to 60 lb. Cover



### CASSETTE FEEDING UNIT-AT1

- 1,650-sheet capacity
- Supports up to Legal
- Supports 16 lb. Bond to 60 lb. Cover



### CASSETTE MODULE-AJ1\*\*

- Desktop configuration
- 550-sheet capacity
- Supports up to Legal
- Supports 16 lb. Bond to 60 lb. Cover

\*Finisher cannot be added after purchase.

\*\*Can add up to two additional cassettes.

# SPECIFICATIONS

## Main Unit

### Type

Colour Laser Multifunctional

### Core Functions

Print, Copy, Scan, Send, Store, Fax

### Processor

Canon Dual Custom Processor (Shared)

### Control Panel

10.1" TFT LCD WSVGA Colour Flat-panel

### Memory

4.0 GB RAM

### Hard Disk Drive

250 GB

### Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T,  
Wireless LAN (IEEE 802.11 b/g/n)

Optional: NFC, Bluetooth Low Energy

Others

Standard: USB 2.0 x1 (Host), USB 3.0 x1 (Host),  
USB 2.0 x1 (Device)

Optional: Copy Control Interface

### Paper Capacity (LTR, 20 lb. Bond)

Standard: 650 Sheets

Maximum: 2,300 Sheets

### Paper Sources (LTR, 20 lb. Bond)

Standard: 550-sheet Paper Cassette, 100-sheet Stack  
Bypass

Optional: 1,650-sheet Paper Cassette  
(Cassette Feeding Unit-AT1)  
550-sheet Paper Cassette  
(Cassette Feeding Unit-AS-1)

### Paper Output Capacity (LTR, 20 lb. Bond)

Standard

Model: 400 Sheets

Finisher: 900 Sheets (400 sheets: base tray, 400

Model: sheets: upper tray, 100 sheets: lower tray)

### Finishing Capabilities

Standard

Model: Collate, Group

Finisher

Model: Collate, Group, Offset, Staple

### Supported Media Types

Stack Bypass: Thin, Plain, Recycled, Heavy, Colour, Bond,  
Envelope

Cassette: Thin, Plain, Recycled, Heavy, Colour, Label,  
Bond

### Supported Media Sizes

Stack Bypass: Legal, Letter, Executive, Statement,  
Envelopes [No.10 (COM10), Monarch, DL,  
ISO-C5], Custom size: 3" x 5" to 8-1/2" x 14"  
(76 x 127 mm to 215.9 mm x 355.6 mm)

Cassette: Legal, Letter, Executive, Statement,  
Custom Size: 4" x 5-7/8" to 8-1/2" x 14"  
(101.6 mm x 148 mm to 215.9 mm x 355.6 mm)

### Supported Media Weights

Cassettes: 16 lb. Bond to 60 lb. Cover (60 to 163 g/m<sup>2</sup>)

Stack Bypass: 16 lb. Bond to 80 lb. Cover (60 to 216 g/m<sup>2</sup>)

Duplex: 16 lb. Bond to 60 lb. Cover (60 to 163 g/m<sup>2</sup>)

### Print/Copy Speed (BW and Colour)

C475iF III / Up to 50 (Letter), Up to 39 (Legal)

C475iFZ III:

### Warm-up Time

From Power On: Approx. 10 Seconds<sup>3</sup>

From Sleep: Approx. 10 Seconds<sup>4</sup>

Mode:

Quick Start-up: Approx. 4 Seconds<sup>5</sup>

Mode:

### Dimensions (W x D x H)

Standard: 20-1/2" x 25-3/8" x 26-3/8"

Model: (521 mm x 645 mm x 668 mm)

Finisher: 20-1/2" x 25-3/8" x 34"

Model: (521 mm x 645 mm x 864 mm)

### Dimensions (W x D x H) with Paper Feeding Unit

Standard Model: 25-1/4" x 26-3/8" x 44-1/4"  
(642 mm x 668 mm x 1124 mm)

Finisher Model: 25-1/4" x 26-3/8" x 52"  
(642 mm x 668 mm x 1320 mm)

### Installation Space (W x D)

37-3/8" x 33-1/8" (950 mm x 840 mm)

### Weight<sup>6</sup>

Standard

Model: Approx. 101.4 lb. (46 kg)

Finisher Model: Approx. 121.3 lb. (55 kg)

## Print Specifications

### Print Resolution (dpi)

1200 x 600

### Standard Page Description Languages

UFR II, PCL<sup>6</sup>, Adobe<sup>®</sup> PS<sup>®</sup> 3

### Direct Print

Available from USB, Advanced Box, Remote UI,  
and Web Access<sup>7</sup>

### Supported File Types

PDF, TIFF, JPEG, EPS, XPS

### Printing from Mobile Devices and Cloud-based Services

A range of software and MEAP-based solutions are available to provide printing from mobile devices or Internet-connected devices and cloud-based services depending on your requirements.<sup>8</sup>

### Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,  
Andalé Mono WT J/K/S/T (Japanese,  
Korean, Simplified and Traditional Chinese),<sup>9</sup>  
Barcode Fonts<sup>10</sup>

PS fonts: 136 Roman

### Operating System<sup>11</sup>

UFR II/PS: Windows<sup>®</sup> 7/8.1/10, Windows Server 2008/  
2008 R2/2012/2012 R2/2016, MAC OS X  
(10.9 or later)

PCL: Windows 7/8.1/10, Windows Server  
2008/2008 R2/2012/2012 R2/2016

PS: Windows 7/8.1/10, Windows Server  
2008/2008 R2/2012/2012 R2/2016,  
MAC OS X (10.9 or later)

PPD: Windows 7/8.1/10, MAC OS X (10.3.9 or later)

## Copy Specifications

### First-Copy-Out Time (LTR)

C475iF III/  
C475iFZ III:

As Fast as 5.1/5.8 Seconds

### Copy Resolution (dpi)

600 x 600

### Multiple Copies

Up to 9,999

### Magnification

25%-400% (1% Increments)

### Preset Reductions

25%, 50%, 64%, 78%

### Preset Enlargements

129%, 200%, 400%

### Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper  
Setting, Previous Settings, Favorite Settings, Finishing,  
Two-sided, Density Adjustment, Original Type Selection,  
Interrupt Mode, Setting Confirmation/Cancel

### Special Copy Features

Two-sided Original, Finishing, Job Build, N on 1, Different Size  
Originals,<sup>12</sup> Density Adjustment, Original Type Selection, Page  
Numbering, Copy Set Numbering, Sharpness, Erase Frame,  
Secure Watermark, Print Date, Shift, Job Done Notice, Copy  
ID Card, Skip Blank Pages, Multi-Sheet Feed Detection,  
Adjust One-Touch Colour, Colour Balance

## Scan Specifications

### Type

Single-pass Duplexing Automatic Document Feeder<sup>13</sup>

### Document Feeder Paper Capacity

100 Sheets (20 lb. Bond)

### Document Feeder Supported Media Sizes

Legal, Letter, Statement, Custom Size: 4-1/8" x 5-7/8" to  
8-1/2" x 14" (105 mm x 148 mm to 216 mm x 355.6 mm)

### Document Feeder Supported Media Weights

BW Original: 1-sided scanning: 12 to 33 lb. Bond  
(42 to 128 g/m<sup>2</sup>)

2-sided scanning: 13 to 33 lb. Bond  
(50 to 128 g/m<sup>2</sup>)

Colour Original: 1-sided scanning: 17 to 33 lb. Bond  
(64 to 128 g/m<sup>2</sup>)

2-sided scanning: 17 to 33 lb. Bond  
(64 to 128 g/m<sup>2</sup>)

### Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height: Up to 1-1/4"  
(30 mm), Weight: Up to 4.4 lb. (2kg)]

### Pull Scan

Colour Network ScanGear2 for both Twain and WIA

Supported OS: Windows 7/8.1/10/  
Server 2008/Server 2008 R2/  
Server 2012/Server 2012 R2/Server 2016

### Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,  
200 x 100, 150 x 150, 100 x 100

### Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to  
mobile devices and cloud-based services depending on  
your requirements.

### Scan Speed (LTR)

Single-sided Scanning (BW and Colour):

50 ipm (300 dpi)/50 ipm (600 dpi)

Double-sided Scanning (BW and Colour):

100 ipm (300 dpi)/50 ipm (600 dpi)

## Send Specifications

### Destination

Standard: Email/Internet Fax (SMTP),  
SMB v3.0, FTP, WebDAV, Mail  
Box, Super G3 Fax  
IP Fax

Optional:

### Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

### Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,  
200 x 100, 150 x 150, 100 x 100

### Communication Protocol

File: FTP (TCP/IP), SMB v3.0, WebDAV

Email: SMTP, POP3

### File Format

Standard: TIFF, JPEG, PDF (Compact, Searchable,  
Apply policy, Optimize for Web, PDF  
A/1-b, Encrypted, Device Signature), XPS  
(Compact, Searchable, Device Signature),  
Office Open XML (PowerPoint, Word)

Optional: PDF (Trace & Smooth, User Signature), XPS  
(User Signature)

### Universal Send Features

Original Type Selection, Two-sided Original, Different-size  
Originals,<sup>12</sup> Density Adjustment, Sharpness, Erase Frame, Job  
Build, Sender's Name (TTI), Delayed Send, Preview, Job Done  
Notice, File Name, Subject/Message, Reply-to, E-mail Priority,  
TX Report, Original Content Orientation, Skip Blank Pages,  
Multi-Sheet Feed Detection

## Fax Specifications

### Maximum Number of Connection Lines

1

### Modem Speed

Super G3: 33.6 Kbps

G3: 14.4 Kbps

### Compression Method

MH, MR, MMR, JBIG

### Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

### Sending and Recording Size

Statement to Legal

### Fax Memory

Up to 30,000 Pages

### Speed Dials

Max. 200

## Group Dials/Destinations

Max. 199 Dials

## Sequential Broadcast

Max. 256 Addresses

## Memory Backup

Yes

## Fax Features

Original Type Selection, Two-sided Original, Density for Scanning, Sharpness, Erase Frame, Job Build, Sender's Name (TTI), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Multi Sheet Feed Detection

## Store Specifications

### Mail Box Simple (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

### Advanced Box

Communication Protocol: SMB or WebDAV Supported

Client PC: Windows 7/8.1/10

Concurrent Connections (Max.)

SMB: 64

WebDAV: 3 (Active Sessions)

### Advanced Box Available Disc Space

Approx. 16 GB

### Advanced Box Features

Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

### Memory Media

Standard: USB

## Security Specifications

### Authentication

Standard: Universal Login Manager (Device and Function Level Log-in), uniFLOW Online Express,<sup>14</sup> User Authentication, Department ID Authentication, Access Management System

Optional: uniFLOW

## Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup, McAfee Embedded Control<sup>19</sup>

Optional: IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

## Network

Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

## Document

Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature, Secure Watermark

Optional: User Signatures

## Environmental Specifications

### Operating Environment

Temperature: 50 to 86 °F

Humidity: 20 to 80 % RH (Relative Humidity)

### Power Requirements

120-127V AC 60 Hz, 8.4 A

### Plug (Main Unit)

NEMA 5-15P

### Power Consumption

Maximum: Approx. 1,500 W

Standby: Approx. 54.3 W<sup>15</sup>

Sleep Mode: Approx. 1.0 W<sup>15</sup>

Typical Electricity Consumption (TEC) Rating<sup>17</sup>

0.54 kWh

### Standards

ENERGY STAR® Certified

## Consumables

### Toner Cartridge

TONER T04 BK/C/M/Y

### Toner Yield

TONER T04 BK: 33,000 pages<sup>18</sup>

TONER T04

C/M/Y: 27,500 pages<sup>18</sup>

<sup>1</sup> Subscription to a third-party cloud service required. Subject to third-party cloud service providers' terms and conditions.

<sup>2</sup> Requires additional option.

<sup>3</sup> Time from device power-on, until copy ready (not print reservation).

<sup>4</sup> Time from exiting Sleep mode to when printing is operational.

<sup>5</sup> Time from device power-on to when copy jobs can be programmed.

<sup>6</sup> Includes consumables.

<sup>7</sup> PDF print from Web sites is supported.

<sup>8</sup> For more information, including compatibility, please visit <http://www.canon.ca>

<sup>9</sup> Requires the optional PCL International Font Set-A1.

<sup>10</sup> Requires the optional Barcode Printer Kit-D1.

<sup>11</sup> Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

<sup>12</sup> Only for Letter/Legal.

<sup>13</sup> Detect Feeder Multi Sheet Feed is supported.

<sup>14</sup> No charge for this solution; however activation is required.

<sup>15</sup> Reference value (measured one unit).

<sup>16</sup> 0.8 W sleep mode not available in all circumstances due to certain settings.

<sup>17</sup> Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.0.

<sup>18</sup> Toner Cartridge yield in accordance with ISO/IEC 19798.

<sup>19</sup> Requires Unified Firmware Platform v3.9

For detailed specifications and a comprehensive list of optional accessories, see the imageRUNNER ADVANCE C475iF III Series Specifications document.

 WWW.CANON.CA



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR guidelines for energy efficiency. The ENERGY STAR mark is a registered mark in Canada. McAfee and the McAfee logo are trademarks of McAfee LLC in Canada and/or other countries. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks of Canon Inc. in Canada and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. "III" indicates that this model has been upgraded to new system software and includes additional security features as standard. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon Canada Inc. does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with a Canon Sales Representative or a Canon Authorized Dealer for details. All printer output images are simulated. Products are shown with optional accessories. Specifications and availability subject to change without notice.

©2019 Canon Canada Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.

0218W789

To learn about Canon's many awards, visit [www.canon.ca/awards](http://www.canon.ca/awards)

